

EVBox Smart Charging














Makes the most efficient use of the available power capacity by safely balancing the energy usage between your electric car charging station and other appliances on-site.

Enables your EV charging to become more self-sufficient and eco-friendly by integrating with your solar installation.*

Gives you full control over your energy usage by providing real-time data on your EV charging and solar production.*

*Available with EVBox Smart Charging+

-  Dynamic load balancing
-  Integrated with solar
-  Peak shaving
-  Universally compatible
-  Easy installation
-  Easy to upgrade
-  CE- and UL-certified
-  Award-winning design
-  Control with mobile app
-  Remote software updates
-  Always online



EVBox Smart Charging kit




1-phase and 3-phase versions available

EVBox Smart Charging safely balances the energy usage between your electric car charging station and other appliances on-site. This ensures your electric car charges in the most efficient way based on the available power capacity, saving you from the costs of any grid upgrades.



Wi-Fi Connect



CT Hub



Power Box



Current transformers

+ Other tools to get you started.


EVBox Smart Charging+ kit

1-phase and 3-phase versions available

EVBox Smart Charging+ connects your electric car charging station with your solar installation and gives you full control over your energy usage. This enables your charging station to make efficient and cost-effective use of the available (self-generated) power.



Genius



CT Hub



Power Box



Current transformers

+ Other tools to get you started.



EVBox Smart Charging



Wi-Fi Connect

Gateway Module

Dimensions	55 mm x 55 mm x 26.6 mm (2.17 x 2.17 x 1.05 inches)
Weight	45 g (1.59 oz)
Operating temperature	-10°C to 60°C (14°F to 140°F)
Humidity	max. 95% non-condensing
Operating altitude	< 2,000 m (6,562 ft)
Standards	IEC-61326-1, FCC 47 part 15, IEC-60950-1
Enclosure ratings	IP X0
Overvoltage conditions	Overvoltage category II
Intended environment conditions	Pollution degree 2
Connectivity	Wi-Fi 2.4 GHz
Included accessories	Wall mounting plate, Bus cable 150 cm (59 inches)

EVBox Smart Charging+

Genius

Gateway Module

Dimensions	108 × 69 × 25 mm (4.25 × 2.72 × 0.98 inches)
Weight	119 g (4.20 oz)
Operating temperature	-10°C to 60°C (14°F to 140°F)
Humidity	max. 95% non-condensing
Operating altitude	< 2,000 m (6,562 ft)
Standards	IEC-61326-1, FCC 47 part 15, IEC-60950-1
Enclosure ratings	IP X0
Overvoltage conditions	Overvoltage category II
Intended environment conditions	Pollution degree 2
Connectivity	Ethernet 100BASE-T, Wi-Fi 2.4 GHz, RF433MHz/915 MHz, Bus B
Included accessories	Wall mounting plate, Bus cable 150 cm (59 inches)

EVBox Smart Charging & EVBox Smart Charging+ CT Hub



Connectivity	Bus A, 4 inputs for split core CTs (50 A, 100 A, 200 A)
Dimensions	70 × 31 × 23 mm (2.75 × 1.22 × 0.90 inches)
Weight	29 g (1.02 oz)
Operating temperature	-10°C to 70°C (14°F to 158°F)
Relative humidity	max. 95% non-condensing
Operating altitude	< 2,000 m (6,562 ft)
Standards	IEC-61326-1, FCC 47 part, IEC61010-1:2010
Enclosure ratings	IP X0, IK 06
Overvoltage conditions	overvoltage category II
Intended environment conditions	Pollution degree 2
Included accessories	Bus cable 40 cm (15.75 inches)

EVBox Smart Charging & EVBox Smart Charging+ Split Core CTs

The necessary quantity and type of split core current transformers are automatically included based on the kit purchased.

Type	50 A	50 A
Cable length	150 cm / 59.06 inches	30 cm / 11.81 inches
Article number	AC-CT-50A	AC-CT-S-50A
L × W × H (mm)	25.5 × 10.5 × 26	25.5 × 10.5 × 26
L × W × H (inches)	1 × 0.41 × 1.02	1 × 0.41 × 1.02
Max. wire diameter	10 mm / 0.39 inches	10 mm / 0.39 inches

EVBox Smart Charging & EVBox Smart Charging+ Solid Core 3-Phase CT

Input current	3 × 50 A
Dimensions	59 × 35 × 23 mm (2.32 × 1.38 × 0.91 inches)
Weight	45 g (1.59 oz)
Operating temperature	-10°C to 70°C (14°F to 158°F)
Relative humidity	max. 95% non-condensing
Standards	IEC-61326-1, FCC 47 part 15
Connectivity	Bus A
Included accessories	Bus cable 40 cm (15.75 inches)



EVBox Smart Charging & EVBox Smart Charging+ Power Box



Electrical properties

Power supply input	90–264 V AC
Power consumption	8 W max
Frequency	50/60 Hz
Voltage measurement inputs	L1, L2, L3, N
Topology and maximum nominal ranges	Single phase: 240 Vrms Split phase: 120/240 Vrms Three phase 3 wires: 240 Vrms Three phase 4 wires: 240/415 Vrms
Overvoltage conditions	Overvoltage category II
Connectivity	Bus A and B

Safety and certification

Operating temperature	-10°C to 50°C (14°F to 122°F)
Relative humidity	max. 95% non-condensing
Operating altitude	< 2,000 m (6,562 ft)
Standards	IEC-61326-1, FCC 47 part 15, IEC61010-1:2010/COR1:2011
Enclosure ratings	IP X0, IK 06
Intended environment conditions	Pollution degree 2

Physical properties

Dimensions	55 × 55 × 26.6 mm (2.17 × 2.17 × 1.05 inches)
Weight	44 g (1.55 oz)
Included accessories	DIN mounting plate, power cable 90 cm open-ended (35.43 inches), bus termination plug

Copyright © 2019 EVBox Manufacturing B.V. EVBox® and the EVBox logo are registered trademarks. All rights reserved. EVBox has compiled this document to the best of its knowledge but does not warrant that all information provided is error-free; EVBox does not accept liability in that respect. All specifications are approximate only. The limited warranty conditions are stated in the applicable EVBox general terms and conditions. EVBPL_SC_EN_072019 © EVBox Manufacturing B.V.

EVBox Manufacturing B.V.
Fred. Roeskestraat 115
1076 EE Amsterdam
The Netherlands
evbox.com/support

